

Lubricants

Haynes (see Haynes tear sheets for more information)

Lubri-Film Tube

4.oz. Tubes, 12 oz. Cartridge, Drums



Description

Heavy duty lubricating grease with high load bearing, low friction properties for all incidental food contact food processing equipment.

Application: Positive pumps, Homogenizer pistons, Size reduction equipment Beverage Equipment, Freezers, Stainless steel threads, Separators, Clarifiers.

Pack

Unit

12

4oz tube

Lubri-Film Spray

11.25oz. Spray



Heavy duty lubricating grease with high load bearing, low friction properties for all incidental food contact food processing equipment.

Application: Positive pumps, Homogenizer pistons, Size reduction equipment Beverage Equipment, Freezers, Stainless steel threads, Separators, Clarifiers.

6

11.25oz.

Lubri-Film Cartridge

12oz. Cartridge



Heavy duty lubricating grease with high load bearing, low friction properties for all incidental food contact food processing equipment.

Application: Positive pumps, Homogenizer pistons, Size reduction equipment Beverage Equipment, Freezers, Stainless steel threads, Separators, Clarifiers.

1
or
10 pk.

12oz
cartridge

Lubri-Film Plus

4oz. Tubes, Drums, Pails



Heavy duty sanitary lubricant with extended performance, low friction properties specifically designed for longer lubrication intervals.

Applications: Pumps, Perpetual moving slicers, Cheese processing equipment, Dispensing units, Bearings, Packings, Plug valves, Locks, Beverage equipment

4oz.

Haynes 500

14oz. Cartridges, Drums, Pails



Designed specifically for food, meat and bakery plants with high temperature (500°F)/high load bearing applications. Extreme pressure qualities and boundary friction protection.

Application: Pumps, Bearings, Packings, Plug valves, Dispensing units, High load bearing equipment, Ball joints, Universal joints, Meat processing equipment, Perpetual moving slicing equipment

1
or
10 pk.

14oz
cartridge

Haynes CIP Film

4oz. Tubes, Drums, Pails



Specifically formulated for Clean-In-Place systems. Low 120°F melting point ideal for food processing equipment with frequent lubrication intervals.

Applications: Fittings, Positive pumps, Threads, Valves, Multi-Port flow selectors, Plug valves, Sanitary CIP systems, Parts requiring daily lubrication

12

4oz tube