

NOW AVAILABLE AT HARCO



POWDER INDUCTION SYSTEM

POWDER-max

POWDER-max by Ampco Applied Products reduces processing time and provides optimal product consistency with no batch size limitations. An innovative design allows POWDER-max to quickly blend wet and dry ingredients in a single, fully portable unit. POWDER-max combines Ampco's SP Series liquid ring pump and High Shear Blender in-line to facilitate limitless production runs. The fully sanitary design is suitable for food, beverage, pharmaceutical and chemical applications.

Five standard models are available and POWDER-max can be customized for a multitude of processing requirements. Options include: hopper covers, hopper screens, pneumatic valves, explosion proof options, bulk bag connectors, table designs and ZP Series circumferential piston pumps for higher viscosities.



NOW AVAILABLE AT HARCO



POWDER INDUCTION SYSTEM

POWDER-max

POWDER-max Standard Features

- Model SP liquid ring pump
- Ampco shear blender or mixer
- 304 stainless steel base material
- 316L wetted parts
- Dual motor starter – NEMA 4X
- Stainless steel casters
- Powder control valve
- Fluid control valve

For more information, call
1-800-361-5361 or e-mail
sales@harco.on.ca.

Max Flow Rate: 350 GPM / 79.5 M3/hr

Max Powder Induction Rate: 700 lbs/min / 318 kg/min

SPECIFICATION	SHEAR-blend	POWDER-max	DRY-blend	SIMPLE-blend
Ideal operating flow rate (low viscosity)	50 – 510 GPM 11 – 116 m3/hr	30 – 210 GPM 7 – 48 m3/hr	40 – 150 GPM 9 – 34 m3/hr	30 – 210 GPM 7 – 48 m3/hr
Powder feed rates (highly soluble)	Up to 150#/min 68 kg/min	Up to 300#/min 136 kg/min	Up to 150#/min 159 kg/min	Up to 300#/min 147 kg/min
Maximum viscosity	1000 cPs	2500 cPs*	2500 cPs*	2500 cPs*
Dynamic shearing teeth	Yes	Yes	No	No

* May require a supply or take-away pump

