

HSG-Series Hygienic Sight Glass





- · Used widely in the food, dairy, and beverage sanitary processes to view products and fluids
- Can be used in industrial applications when you want to CIP and require 316L stainless steel construction

Sizes

- 1/2" to 6"
 - single pin clamp: 1" to 6"; EPDM or FKM gasket
 - bolted clamp: 1/2" to 6"; PTFE gasket

Features

- · 3A CIP certified
- · Higher pressure range than other sight glasses
- · Easy assembly and disassembly
- Rubber seals are I-line gaskets
- · Clamp protects glass from getting damaged
- Patent pending assembly design

Materials

- · Body: 316L stainless steel
- · Sight glass: polycarbonate
- · Gaskets: PTFE, EPDM, or FKM



Bolted Clamp





Part Number Key

Series	Elastomer 1	Size	Body One Connection	Body Two Connection	Surface Finish
		050 = 1/2" 2			
		075 = 3/4" 2			
		100 = 1"	C = triclamp	C = triclamp	
	E = EPDM	150 = 1-1/2"	B = weld F = female I-line	B = weld F = female I-line	A = ≤32 Ra (ID mechanical polish) B = ≤25 Ra (ID mechanical polish)
HSG	V = FKM	200 = 2"	M = male I-line	$M = \text{male I-line}$ $M = \text{male I-line}$ $C = \le 20 \text{ Ra (ID me}$ $T = \text{threaded bevel}$ $D = \le 15 \text{ Ra (ID ele}$	C = ≤20 Ra (ID mechanical polish)
	P = PTFE	250 = 2-1/2"	T = threaded bevel P = plain bevel with nuts		D = ≤15 Ra (ID electropolish) E = ≤10 Ra (ID electropolish)
		300 = 3"	Q = Q-line	Q = Q-line	L - STO Na (ID electropolish)
		400 = 4"			
		600 = 6"			

 $^{^{\}rm 1}$ EPDM or FKM with single pin clamp, PTFE with bolted clamp $^{\rm 2}$ 1/2" and 3/4" available only with PTFE elastomers

Pressure Ratings

Size	PSI @ 70°F (21°C)	PSI @ 200°F (93°C)
1/2" - 1"	500	300
1-1/2"	450	250
2"	400	200
2-1/2"	350	175
3"	250	125
4"	80	40
6"	50	25

NOTE: Repair kits consisting of two gaskets are available for all sizes and configurations.

