



The Classic Dairy Valve


Alfa Laval D10 and D11 Plug Valves

Application

The bonded rubber or stainless steel plug valves are used in food and chemical industries and in other installations where a sanitary closing device with minimum pressure drop is required. D10 and D11 plug valves are designed for quick and easy operation. The D10 is a two-way valve, and the D11 is a three-way valve.

Standard Design

The plug valves are made of stainless steel AISI 304. They are produced with a strong, rigid body made from drop forged homogeneous material, and the plug is rubber coated. An optional chrome plated and lapped metal plug is available. The plug valves may be supplied with weld connections, clamps or threaded connections.



TECHNICAL DATA

D10F and D10FL legal tank pasteurization valve

Ordering

Please state the following when ordering:

- Connections
 Tri-Clamp®, Bevel Seat, weld
- Tri-Clamp®, Bevel Seat, weld
 Type
- Plug Bonded rubber (Buna) or stainless steel. D10FL only available with stainless steel plug


Straight-through valve D10, three-way valve D11, tank outlet valve


Size
 Following sizes are available: 1-inch, 1.5-inch, 2-inch, 2.5-inch, 3-inch

PHYCICAL DATA

Materials


Steel parts AISI 304
Finish ≤ Ra 32 µin
Rubber parts Buna (N)






Dimensions Tri-Clamp® connections


Size (Tube OD)		Α		В		С		D		E		Approx. Wt.	
inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	lb	kg
1½	38.1	229/32	73.8	5 ¹³ / ₁₆	147.6	7	177.8	$5^{5}/_{8}$	142.9	21/2	63.5	9.50	4.30
2	50.8	31 ³ / ₃₂	86.5	6 ¹³ / ₁₆	173.0	7 ⁵ / ₈	193.7	5 ⁵ / ₈	142.9	27/8	73.0	15.50	7.03
21/2	63.5	41/8	104.8	81/4	209.6	83/4	222.3	61/4	158.8	31/2	88.9	25.50	11.56
3	76.2	423/32	119.9	97/16	239.7	93/4	247.7	71/4	184.2	33/4	95.3	36.00	16.32






Dimensions Weld connections


Size (Tu	be OD)	Α		В		С		D		E		Approx. Wt.	
inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	lb	kg
11/2	38.1	223/32	69.1	5 ⁷ / ₁₆	138.1	$6^{7}/_{8}$	177.8	5 ⁵ / ₈	142.9	21/2	63.5	9.50	4.30
2	50.8	33/16	81.0	$6^{3}/_{8}$	161.9	7 ⁵ /8	193.7	$5^{5}/_{8}$	142.9	$2^{7}/_{8}$	73.0	15.50	7.03
21/2	63.5	47/8	123.8	73/4	196.9	8 ⁵ /8	222.3	61/4	158.8	31/2	88.9	25.50	11.56
3	76.2	415/32	113.5	8 ¹⁵ / ₁₆	227.0	93/4	247.7	71/4	184.2	33/4	95.3	36.00	16.32






Dimensions Bevel Seat connections

Size (Tube OD)		Α		В		С		D		E		Approx. Wt.	
inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	lb	kg
11/2	38.1	229/32	73.8	5 ¹³ / ₁₆	147.6	6 ⁷ / ₈	174.6	5 ⁵ / ₈	142.9	21/2	63.5	9.50	4.31
2	50.8	313/32	86.5	6 ¹³ / ₁₆	173.0	75/8	193.7	5 ⁵ /8	142.9	27/8	73.0	15.50	7.03
21/2	63.5	41/8	104.8	81/4	209.6	8 ⁵ / ₈	219.1	61/4	158.8	31/2	88.9	25.50	11.56
3	76.2	423/22	119.9	97/16	239 7	93/4	247.3	71/4	184 2	33/4	93.7	36.00	16.33







Dimensions (inches) Plug Valve Tank - D10F and D10FL

Size (Tube OD)	Α	В	С	D	E	F	G	Н	I	J	K	Hole Size	Appro	x. Wt.
1½	4 ⁵ / ₁₆	31/8	5 ⁵ /8	23/8	63/4	123/32	37/16					9/16	9.50	4.30
2	5 ⁷ /16	41/8	5 ⁵ /8	23/4	71/2	21/8	41/4					⁹ /16	15.50	7.03
21/2	63/4	45/8	61/4	31/2	83/4	$2^{5}/_{8}$	51/4	1 ⁵ / ₁₆	11/2	21/2	5	9/16	25.50	11.56
3	8	43/4	71/4	33/4	93/4	3 ⁵ / ₁₆	6 ⁵ /8	13/4	13/4	2 ¹³ / ₁₆	5 ⁵ /8	11/16	36.00	16.32

Dimensions (mm) Plug Valve Tank - D10F and D10FL

Size (Tube OD)	Α	В	С	D	E	F	G	Н	I	J	к	Hole Size	Approx	. Wt.
1½	109.5	79.4	142.9	60.3	171.5	43.7	87.3					14.3	9.5	4.30
2	138.1	104.8	142.9	69.9	190.5	54.0	108.0					14.3	15.5	7.03
21/2	171.5	117.5	158.8	88.1	222.3	66.7	133.4	33.3	38.1	63.5	127.0	14.3	25.5	11.56
3	203.2	120.7	184.2	95.3	247.7	84.1	168.3	44.5	44.5	71.4	142.9	17.5	36.0	16.32



Alfa Laval reserves the right to change specifications without prior notification. ALFA LAVAL is a trademark registered and owned by Alfa Laval Corporate AB.

ESE00518ENUS 1112

© Alfa Laval

How to contact Alfa Laval

Contact details for all countries are continually updated on our website. Please visit www.alfalaval.us to access the information direct.