

Stainless Steel Ball Valves

FULL PORT

Harco offers a full-line of Dixon manual ball valves that are for applications using water, oil, and gas. A number of sizes and connection types are available.

Stainless Steel Ball Valves Full Port

SSBV#

Features

- Blow-out proof stem design

Material

- 316 stainless steel ball and stem
- RPTFE seat, joint gasket, and thrust washer
- Plastic cover on handle

Specifications

- Temperature range: -20°F to 300°F (-29°C to 149°C) as long as the valve is run fully open/closed
- Pressure rating:
1/4" - 2" rated to 1000 PSI WOG (CWP)
2-1/2" - 3" rated to 800 PSI WOG (CWP)
100 PSI saturated steam



Full Port Ball Valves with Locking Handle

SSLBV#

Features

- Lockable
- Blow-out proof stem design
- Not recommended as a throttling valve

Material

- 316 stainless steel ball and stem
- RPTFE seat, joint gasket, and thrust washer
- Plastic cover on handle

Specifications

- Temperature range:
-20°F to 356°F (-29°C to 180°C)
- Pressure rating:
1/4" - 2" rated to 1000 PSI WOG (CWP)
2-1/2" - 3" rated to 800 PSI WOG (CWP)
100 PSI saturated steam



The Right Connection®

**Contact us today for a quote,
1-800-361-5361 or sales@harco.on.ca.**

www.harcosupply.com

675 The Parkway,
Peterborough, Ontario K9J 7K2

**800-361-5361
705-743-5361
sales@harco.on.ca**